



DIN 551
ISO 4766

Gewindestifte mit Schlitz und Kegelkuppe

Slotted set screws with flat point
Vis sans tête, fendue, à bout plat

A 2
AISI 304



t min.	0,64	0,72	0,8	1,12	1,28	1,6	2	2,4
n	0,25	0,4	0,4	0,6	0,8	1	1,2	1,6
d ₁	1	1,5	2	2,5	3,5	4	5,5	7
d	M 2	M 2,5	M 3	M 4	M 5	M 6	M 8	M 10
l (mm)								
2	31,90							
3	18,50	16,30	14,10					
4	18,90	17,60	9,45	10,10	13,10			
5	21,-	18,90	10,10	10,30	11,40	17,40		
6	22,80	20,40	10,90	10,90	12,20	13,-	31,90	
8	23,50	21,40	11,60	11,70	13,-	13,90	22,80	
10	25,-	22,10	12,20	12,60	13,90	15,-	23,20	37,50
12	26,50	24,50	12,80	13,20	15,-	16,30	25,90	37,50
16	29,90	26,50	13,70	14,10	16,50	17,50	28,90	40,30
20			16,10	16,90	20,10	20,60	35,-	52,10
25				20,40	23,-	24,20	42,-	59,80
30				23,10	25,70	28,90	46,60	64,90
35				26,80	35,-	33,20	49,70	69,50
40					39,30	37,50	53,60	74,60
45						44,40	59,80	80,70
50						53,60	67,40	88,90
60						61,80	98,60	148,-
70						73,10	116,-	191,-
80							140,-	242,-
	200	200	200	200	200	200 ab 45 100	100 ab 60 50	50 ab 70 25

€ Preise / Prices / Prix ... 100 Stück / pcs.

Bestellbeispiel / example for ordering / exemple de commande: **DIN 551 - A 2 - M 2 x 3**

Ab M 12 empfehlen wir den Einsatz von Gewindestiften mit Innensechskant nach DIN 913.

From M 12 on we recommend to use hexagon socket set screws with flat point (DIN 913) instead.

A partir du M 12, nous recommandons l'utilisation de vis STHC DIN 913.