



**DIN 553**  
**ISO 7434**

## Gewindestifte mit Schlitz und Spitze

Slotted set screws with cone point  
Vis sans tête à bout pointu, fendue

**A 2**  
**AISI 304**



t min.	0,64	0,72	0,8	1,12	1,28	1,6	2	2,4
n	0,25	0,4	0,4	0,6	0,8	1	1,2	1,6
d <sub>1</sub>	0,2	0,25	0,3	0,4	0,5	1,5	2	2,5
d	<b>M 2</b>	<b>M 2,5</b>	<b>M 3</b>	<b>M 4</b>	<b>M 5</b>	<b>M 6</b>	<b>M 8</b>	<b>M 10</b>
l (mm)								
3	18,50	16,30	14,10					
4	18,90	17,60	9,45	10,10				
5	21,-	18,90	10,10	10,30	11,40			
6	22,80	20,40	10,90	10,90	12,20	13,-		
8	23,50	21,40	11,60	11,70	13,-	13,90	22,80	
10	25,-	22,10	12,20	12,60	13,90	15,-	23,20	37,50
12			12,80	13,20	15,-	16,30	25,90	37,50
16			13,70	14,10	16,50	17,50	28,90	40,30
20			16,10	16,90	20,10	20,60	35,-	52,10
25				20,40	23,-	24,20	42,-	59,80
30				23,10	25,70	28,90	46,60	64,90
35					35,-	33,20	49,70	69,50
40						37,50	53,60	74,60
45							59,80	80,70
50							67,40	88,90
	<b>200</b>	<b>200</b>	<b>200</b>	<b>200</b>	<b>200</b>	<b>200</b>	<b>100</b>	<b>50</b>

€ **Preise** / Prices / Prix ... 100 Stück / pcs.

**Bestellbeispiel** / example for ordering / exemple de commande: **DIN 553 - A 2 - M 8 x 12**

**Ab M 12 empfehlen wir den Einsatz von Gewindestiften mit Innensechskant nach DIN 914.**

From M 12 on we recommend to use hexagon socket set screws with cone point (DIN 914) instead.

A partir du M 12, nous recommandons l'utilisation de vis STHC DIN 914.