



Gewindestifte mit Schlitz und Spitze

Slotted set screws with cone point
Vis sans tête à bout pointu, fendue

DIN 553
ISO 7434

A 4
AISI 316



t min.	0,8	1,12	1,28	1,6	2	2,4
n	0,4	0,6	0,8	1	1,2	1,6
d ₁	0,3	0,4	0,5	1,5	2	2,5
d	M 3	M 4	M 5	M 6	M 8	M 10
l (mm)						
3	16,-					
4	15,-	13,10				
5	16,-	14,10	13,90			
6	17,-	15,-	17,70	21,10		
8	18,70	17,30	20,10	24,-	33,40	
10	20,50	19,40	22,70	27,20	33,80	47,50
12	24,20	21,60	25,20	30,30	37,50	53,10
16	28,20	25,90	30,20	36,40	44,70	63,30
20	32,-	30,10	35,20	42,70	52,10	74,10
25		36,40	42,70	50,50	59,30	89,40
30		40,80	47,80	58,20	70,-	100,-
35				65,90	79,20	113,-
40				73,60	88,40	126,-
45					97,10	139,-
50					106,-	152,-
	200	200	200	200	100	50

€ **Preise** / Prices / Prix ... 100 Stück / pcs.

Bestellbeispiel / example for ordering / exemple de commande: **DIN 553 - A 4 - M 6 x 40**

Ab M 12 empfehlen wir den Einsatz von Gewindestiften mit Innensechskant nach DIN 914.

From M 12 on we recommend to use hexagon socket set screws with cone point (DIN 914) instead.

A partir du M 12, nous recommandons l'utilisation de vis STHC DIN 914.